



www.csiro.au

Phased Array Feed Receiver Development for the Australia SKA Pathfinder


R. Gough, J. O'Sullivan, S. Hay, A. Chippendale and R. Qiao
CSIRO Australia Telescope National Facility and CSIRO ICT Centre

November 16-17, 2009



The team drawn from ATNF and ICT

- **Modelling**
 - Stuart Hay, Rong-Yu Qiao, Francis Cooray, John O'Sullivan
- **Antenna Measurements**
 - Leigh Stokes, Doug Hayman
- **Analogue and Signal Distribution**
 - Russell Gough, Russ Bolton, Paul Doherty, Kanapathippillai Jeganathan, Simon Mackay, Rob Shaw, Peter Axtens, Suzy Jackson, Chris Cantrall
- **Antenna and Mechanical**
 - Mike Kesteven, Carol Jackson, Ross Forsyth, Deszo Kiraly
- **Digital**
 - John Bunton, Tim Bateman, Jayasri Joseph, Joseph Pathikulangara, Grant Hampson, Andrew Brown
- **Computing and software, observing**
 - Juan Carlos Guzman, Tony Maher, Shaun Amy, Aaron Chippendale, Michael Brothers
- **Parkes team**
 - John Reynolds, Brett Presig, Tim Ruckle, Brett Armstrong
- **Project Management**
 - Steve Barker, Mark Bowen, Alan Ng



Outline

- **Introduction**
 - ASKAP specifications
 - Murchison Radio Observatory
 - The ASKAP antenna specification
 - Advantages focal plane arrays over an array of feed horns
- **ASKAP prototype PAF receiver system**
 - Checkerboard array
 - Analog System specifications
 - Design constraints
- **ASKAP Analog System architecture**
 - Prime Focus package
 - Receiver maintainability
 - Calibration issues
- **Results**
 - Low-noise amplifier
 - Array measurements
 - System temperature estimates
- **Conclusion**
 - Project status


ASKAP specifications

ASKAP Design Goals:


- High-dynamic range
- Wide field-of-view imaging

| | |
|--------------------------|---|
| Number of dishes | 36 |
| Dish diameter | 12 m |
| Max baseline | 6 km |
| Resolution | 30" |
| Sensitivity | 65 m ² /Kelvin |
| Speed | 1.3x10 ⁵ m ⁴ /Kelvin ² /deg ² |
| T_{SYS}/η | 63 Kelvin (eg. $T_{\text{SYS}} = 50$ K, $\eta = 80\%$) |
| Observing frequency | 700 – 1800 MHz |
| Field of View | 30 deg ² |
| Processed Bandwidth | 300 MHz |
| Spectral channels | 16 k |
| Focal Plane Phased Array | 188 receiver channels |

Murchison Radio Observatory




Murchison Radio Observatory




The ASKAP antenna specification

- 12m – prime focus, unshaped
- $f/D = 0.5$
- Alt-Az mount, with 3rd polarisation axis (Sky mount)
- Surface accuracy 1mm RMS
(Operation to 10 GHz)
- Pointing accuracy 30 arcsec
- 2 arcsec alignment of optical axis and polarisation axis
- 45 km/h operational wind speed
- 160 km/h survival wind speed
- Feed mount capable of supporting a 200 kg PAF
- Accommodation for CSIRO equipment, eg, beamformer
- Accommodation for ~200 RF channels (coax) to PAF
- Operation in a desert environment



The ASKAP antenna specification




Advantages focal plane arrays over an array of feed horns


- By choosing the appropriate beamformer element weights we can maximise efficiency, sensitivity or beam quality.
 - **For maximum efficiency**
we choose weights that are the conjugate of the received signal gain on each port.
 - **For maximum sensitivity**
we choose weights as for optimum efficiency (above), but also multiply the weights by the inverse of the noise covariance.
 - **For optimum beam quality**
we choose weights to control the primary beam sidelobes, and cross polarisation.
That is, we choose weights to fit a desired, circularly symmetric reflector aperture illumination.
- We can also optimise a combination of the above: for example, trading-off sensitivity for beam quality.

Checkerboard Array



- ASKAP PAF array size
 - 12 x 12 patches with 6 patches omitted from each corner
 - ~1100 mm diameter



Prototype “5x4” array



Checkerboard Array




Analog System specifications


- **Phased array receiver size**
 - Receiver elements ~200 per antenna
- **Frequencies**
 - RF band 700 – 1800 MHz
 - Instantaneous bandwidth 300 MHz
 - Sampled band 424 – 724 MHz
 - Sample clock 768 MHz
- **Low-noise amplifiers**
 - amplifier noise temperature 40 Kelvin
 - amplifier gain 27 dB
- **System gain**
 - Nominal total net gain 72 dB
- **Output power (to digitiser)**
 - Nominal IF output power -19 ± 1 dBm into 50 Ohms

Receiver design constraints


- Relatively long f/D ratio
(f/D = 0.5)
- PAF receiver weight must be less than 200kg
- High attenuation in coax cable from prime focus to pedestal
 - 17dB at 0.7GHz
 - 31dB at 1.8GHz
- Minimise RFI generated
- Maximise RFI immunity




ASKAP Analog System architecture




Prime Focus package




Prime Focus package




Prime Focus package




Prime Focus package



Prime Focus package



Prime Focus package



Calibration issues

- Calibration

- Calibration signal(s) transmitted from dish surface
- Both polarisations
- Correlate transmitted signal with received signal in each receiver channel

- Gain and Phase stability - post electronic calibration (if any)



- Maximum RMS gain/phase fluctuation in ~ 1 minute *
0.026 dB, 0.16°
- Maximum RMS gain/phase fluctuation in ~ 1 second **
1.4 dB, 10°

* To minimise the residual error sidelobes from sources in the field-of-view (no self-cal within the field-of-view is possible on these short time scales)

** Larger gain/phase fluctuations will cause signal loss through decorrelation

Low-noise amplifier

- Design frequency range:
0.7 – 1.8 GHz
- Design system impedance at input :
300 Ω (differential)
- Low noise transistors:
Avago ATF 35143
- Two stages of gain
Configured as two independent amplifiers with a single (difference) output
- Gain:
28 dB
- Noise temperature:
35 – 55 Kelvin
(measured in a 300 Ω differential system impedance)






Measurement of prototype “5x4” array

- Early days
 - More work need to be done as results are inconsistent
- Typically, the beamformed T_{SYS} is $\sim \frac{1}{4}$ of the single element T_{SYS}
- Characterising array performance as an aperture array
 - Element weighting is different from that when the array is used as a focal plane array
 - “Hot-box” and sky
 - 2.4 m x 3.0 m load
- Estimated T_{SYS}
 - Single element ~ 240 K
 - Beamformed 60-80 K



Measurement of prototype "5x4" array



Astronomical measurements

- Characterising array performance as a Phased Array Feed:
 - Single dish measurements
 - Interferometry measurements with the Parkes 64 metre dish
- Measurements of:
 - Virgo A,
 - 1934-638 and
 - An extended HI region (S9).
- Best estimate
 - Single element $T_{\text{SYS}}/\eta \sim 600\text{K}$ at 1310 MHz
 - Beamformed $T_{\text{SYS}}/\eta \sim 150\text{K}$ at 1310 MHz
 - Phased Array feed results are inconsistent with aperture array results
 - And both results are inconsistent with modelling



Project status

Recent milestones



Dedicated 12m testbed antenna at Parkes for PAF development, commissioned early 2008.




Prototype 5x4 array complete – first light August 2008.



ASKAP Antenna 1
Factory acceptance test
September 2009

Project status

Antenna delivery



Murchison Radio Observatory (MRO)

S26° 42' 15" E116° 39' 32 "

Population density; 1×10^{-9} humans / metre²



Australia Telescope National Facility

Russell Gough

November 16, 2009

Web: www.atnf.csiro.au

www.csiro.au

Thank you

Contact Us

Phone: 1300 363 400 or +61 3 9545 2176
Email: enquiries@csiro.au Web: www.csiro.au

